

## Liberty Select <sup>™</sup> Nurse In-Service Checklist For software versions 2.8.7 and higher



Nurse Participant:	Date	e:
Facility:		
Instructor:		
Note: The following checklist is for Liberty Select    To cyclers wiversions 2.8.2 to 2.8.5, please use part number 101134-01, Liberty Training topics covered in this checklist are based on the manufa and effectively operate the Liberty Select cycler. Other topics list PRGLÀHG WR DFFRPPRGDWH \RXU IDF reviewed during the in-service training, and are not a representation.	iberty Cycler Peritoneal Dialysis In-Service Cheacturer's recommendations on how to safely ed below, not related to machine use, may be LOLW\·V VSHFLAF SROLFLH\	ecklist .  / DQG SURFHG
		l <b>1</b>
	1	, <b>1</b>

Training Topic	Instructor's
	initials
Entering Options Settings	
Select values	
Add diurnal UF	
‡/DQJXDJH (QJOLVK 6SDQLVK RU )UHQFK	
Last bag option	
‡6, XQLWV \HV RU QR	
Personal data	
USB enabled	
Drain exit %	
Add drain	
Add drain alert	
Entering Hardware Settings	
Select values	
Alarm loudness	
Key loudness	
Date format	
Date     Date	
Time format	
• Time	
Screen blanking	
Brightness	
Initiating Treatment	
Check that cycler has been cleaned and disinfected per manufacturer's	
recommendations	
(QVXUH F\FOHU LV SOXJJHG LQWR D JURXQGHG WKUHH	\$URQJHG
power is on	
Check that heater tray is free from obstruction	
9HULI\ WUHDWPHQW YDOXHV RQ '5HDG\µ VFUHHQ	
PressOK key to start treatment	
Gather supplies, mask, and wash hands	
Before inserting the cycler set into the cycler, inspect cycler set for any signs of damage	
WR WXELQJ FODPSV 3,1 FRQQHFWRU V RU ÀOP	
Note: If cycler set is damaged, do not insert into the cycler. Save the cycler set and	
call Technical Support.	
(QVXUH F\FOHU VHW LV SURSHUO\ LQVHUWHG 7KH FDVV	HWWH LV
DQG VQDSSHG LQWR WKH ORZHU FDWFK (QVXUH OLQHV	KDQJ VW
First, carefully insert the top portion of the cassette. Then, press the lower portion in	
until it snaps securely, and close the door.	
‡,QVHUW WKH 3,1 FRQQHFWRU IURP WKH SDWLHQW OLQH	EOXH FO
,QVSHFW DOO VROXWLRQ EDJV LQFOXGLQJ KHDWHU ED.	
lines and properly place heater bag on heater tray	
Review minimum and maximum bag volume	
Connect drain lines or drain bags; touch Next	
Break cones (use stay•safe Handi-tool as necessary)	
Clamp unused lines; touch Next	
•	
Verify bag connections; touch Next	
&\FOHU SHUIRUPV D WXELQJ ÁXVK	